

LKX



CRANKSHAFT



Models: 1515 LP
2015 LP



Equipped with:

- 4 poles electrical motor (1450 RPM) with thermal protection and water cooling (three phase models).
- Three ceramic coated pistons (1 ph), full ceramic pistons (3 ph), brass linear pump head with built-in by-pass valve.
- Low voltage and delayed Total Stop.
- Suction and delivery S. S. valves.
- Vertical burner with high thermal efficiency steel coil.
- Temperature regulation gauge with high sensitive stainless steel sensor.
- Detergent built-in tank (3 lt) for indirect suction.
- Auxiliary motor for burner.
- Heavy duty steel frame.
- Hose reel with brake (**optional**).

STANDARD EQUIPMENT

- 3.700.0030 Gun M22 - 3/8" with rotating coupling.



- 3.701.0015 Lance M22 high/low pres. (mod. 1310 LP)



- 3.103.0050 Nozzle type 045 (mod. 1310 LP)
- 3.103.0053 Nozzle type 060 (mod. 1515 LP)
- 3.103.0050 Nozzle type 045 (mod. 2015 LP)



- 4.618.0143 H. P. hose 10 m



- Power cable 5 m

Optional:

- 6.608.0077 Hose reel with brake (hose not included)
- On request models with header tank and/or antiscaling device.
- 3.697.0044 Antiscaling LC-PRECAL (pcs. 4 x 5 lt.)

Other available versions:

- 8.621.2944 LKX 2015 with header tank
- 8.621.3032 LKX 2015 with header tank and antiscaling device
- 6.602.0042 ROTOX lance (Mod. 1515 LP)
- 6.602.0040 ROTOX lance (Mod. 2015 LP)

| | LKX 1310 LP | LKX 1515 LP | LKX 2015 LP |
|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| code | 8.621.2947 | 8.621.2934 | 8.621.2935 |
| operat. pressure/max | 110/150 bar-1595/2175 psi | 150 bar-2175 psi | 200 bar-2900 psi |
| delivery rate | 660 l/h-2.91 GPM | 900 l/h-3.96 GPM | 900 l/h-3.96 GPM |
| abs. power/voltage | 3000W - 230V~50Hz 1ph | 5500W - 400V~50Hz 3 ph | 7300W - 400V~50Hz 3 ph |
| motor/pump type/RPM | MP3/1450 RPM | MPW3.5/1450 RPM | MPW3.5/1450 RPM |
| max. water inlet/outlet temp. | 40/110 °C | 40/110 °C | 40/110 °C |
| dimension/weight | 94x65x90cm / 112 Kg - 246 lbs | 94x65x90cm / 125 Kg - 275 lbs | 94x65x90cm / 128 Kg - 282 lbs |